

WESTCO FILTERS

Liquid Filter Solutions since 1982

FBFS Series Bag Filter Housing

Westco Model FBFS12 single bag filter housings are designed for flow rates to 100-110 gpm respectively. Our FBFS12 housings take the industry standard #2 size filter bag (7"x32") with 4.4 sq. ft. of total filter surface area. Standard units are non-code.

Standard housings are available in carbon steel, 304 SS and 316 SS with 2" NPT or FLG connections. Our universal style 5 offers dual outlet ports to accommodate ease in piping installation.

Features and Options

- ASME Code and non-code Designs
- Carbon Steel; 304SS, and 316SS Available
- Takes one standard #2 Size Filter Bags
- CS Legs (Standard) SS Adjustable Legs (Optional)
- Single Lid Seal O-Ring Gasket – Buna, EPDM, Viton and Viton-Teflon Encapsulated
- Electro-polish finish - Our optional electro-polish finish makes cleanup easy and takes the mess out of changing bags with a smooth, clean surface on the interior and exterior of our housings. Eliminates residual build-up and makes clean-up fast and easy



FBFS12 housing take the Westco snap tight molded plastic filter bag top which provided a secure bag seat eliminating bypass.

Filter Bags:

Polyester Felt: 0.5, 1, 3, 5, 10, 25, 50, 75, 100, 200 Micron

Polypropylene Felt: 0.5, 1, 3, 5, 10, 25, 50, 75, 100, 200 Micron

Polyester Mesh: 75, 100, 150, 175, 200, 250, 400, 600, 800, 1000, 1500

Nylon Mesh: 1, 5, 10, 25, 35, 45, 50, 75, 100, 125, 150, 200, 250, 300, 400, 600, 800, 1200

Polypropylene Mesh: 150, 200, 250, 300, 400, 600, 800