

WESTCO FILTERS

Liquid Filter Solutions since 1982

1CFH-SS Single Cartridge SOE Housing

Westco offers a complete line of single cartridge filter housings for low flow and batch applications. Designed to take SOE or single open end cartridges for use with cartridges that filter from 0.02 micron to

- Designed for industrial and commercial filter applications
- Heavy duty construction for maximum durability
- 316L Stainless Steel construction with cast head and electro-polished sump suitable for a wide range of process requirements
- Accepts 222 or 226 connector cartridges with Fin or Flat ends
- Available with 3/4", and 1" in-line connections for easy installation
- Ring nut closure for quick cartridge change outs
- Equipped with mounting bracket kit and wrench
- Numerous gasket options for compatibility with most fluids



Applications

Water

Food & Beverage

Oil

Coolants

Chemicals

Electronics

Inks / Paints / Coatings

Pulp & Paper

Specifications & Operating Parameters

Maximum Operating Pressure

300 psig (20.7 bar) @ 200°F (93°C)

Connections

Inlet /Outlet: 3/4" or 1" FNPT

Optional: BSPT, BSPP, RF Flanges, Sanitary Ferrules or Grooved Fittings

Drain Port: 1/4" NPT Plug

Materials of Construction

Head / Shell: 316L Stainless Steel

Gaskets

Buna N

Optional : EPR, Silicone, Viton

Options

- Gauge Port

- Vent Port with Vent Screw

See Ordering Guide for complete selection of options